KP-1020 Digital Access Keypad

Description

A weather-resistant keypad for indoor or outdoor access control. The KP-1020 supports up to 20 individual entry codes plus one toggle code for hold-open operation.

Authorized users can activate a momentary open command or toggle the hold-open function. A request-to-exit input allows exit without entering a code.

Mounts to a standard gooseneck, column, or wall. Nonvolatile memory retains stored data during a power failure.



Features

- 20 entry codes plus 1 toggle code
- Blue backlit keys
- Push button / request-to-exit input
- Programmable entry and master codes
- Three LED status indicators
- Nonvolatile code memory
- Knock outs for flush mounting
- Private Labeling available
- Master Reset button
- Metal housing and stainless steel faceplate

Warranty

One-year warranty against defects in materials and workmanship under normal use from the date of sale to the original purchaser. Warranty is available only through an SGC Authorized Dealer. Product specifications are subject to change without notice.

Dealer Program

Exclusive Sales Territories	No Direct Online Competition
Enforced Price Minimums	Shared Online Leads

Specifications

Operating voltage
12-24V AC/DC

Standby current
50 mA at 12 VDC; 60 mA at 24 VDC

Pull-in current
80 mA at 12 VDC; 100 mA at 24 VDC

Input
Request-to-exit

Relay output
N.O. / N.C. / Common dry contact

Relay rating
3 A at 120 VAC; 3 A at 24 VDC

Backlight
Blue LED; delay setting option

Strike time
1-99 seconds

Strike mode
Access timer or toggle

Code capacity
20 momentary; 1 toggle

Operating temperature
-4°F to 158°F (-20°C to 70°C)

Also available



Long Range Remote



Mini Loop Detector



Pushbutton exit with lockout



Become an authorized dealer
sgcaccess.com

Dealer Program